

Microwave Switch

Model MSS3100



- ◆ High Density Microwave Switch
- ◆ Provides Ultra High Density for RF and Microwave Switching Requirements
- ◆ DC to 18GHz
- ◆ 50Ω Coaxial Switches
- ◆ Direct SMA Front Panel Connections



偉潤科技股份有限公司

WELLRING TECHNOLOGY CO., LTD.

台中市工業區38路210號7F-12

7F-12, NO. 210, 38th Rd., Taichung Industrial Park, Taichung, Taiwan, R.O.C

TEL : 886-4-23580819 FAX : 886-4-23507915

網址 : www.wellring.com.tw

E-Mail : wellring@ms74.hinet.net

MSS3100 SPECIFICATIONS

MODEL	MSS3100
MICROWAVE PERFORMANCE	
FREQUENCY RANGE	DC TO 18 GHz
SWITCHING	36 CHANNEL
VSWR (MAX)	1.50
ISOLATION dB (MIN)	60
INSERTION LOSS dB (MAX)	0.5
RF IMPEDANCE	50 OHMS
SWITCHING TIME	20 ms
USER CONNECTOR	SMA male (not supplied)
ENVIRONMENTAL DATA	
POWER SUPPLY	AC 110~220V \pm 5%, 50/60 Hz
ALTITUDE	15,000 ft
TEMPERATURE	10°C ~ 55°C
HUMIDITY	LESS THAN 95% RELATIVE
SIZE	(W) 430 mm, (H) 128 mm, (D) 360 mm
WEIGHT	2.7 Kg

Specifications are subject to change without notice

規格變更不另通知



偉潤科技股份有限公司

WELLRING TECHNOLOGY CO., LTD.

台中市工業區 38 路 210 號 7F-12

7-12, NO. 210, 38th Rd., Taichung Industrial Park, Taichung, Taiwan, R.O.C

TEL: 886-4-23580819

FAX: 886-4-23507915

網址: www.wellring.com.tw

E-Mail: wellring@ms74.hinet.net